



Mulcher combined of great power for tractors up to 270 HP. Perfect for punctured of maize, sorghum, sunflower, cotton and meadow in big extensions.

It incorporates hydraulic rear hood with turn arble nozzles, to extend the matter uniformly.

Double geardrives of traction, which guarantees a perfect transmission of power between the tractor and the rotor. Rotor POLSER of 725 mm of diameter equipped with different elements of cut: blades or hammers.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 10 mm.
- ▶ Rotor POLSER of Ø 725 mm.
- ▶ Gearboxwith freewheel up to 270 HP.
- ▶ 2 x 4 XPC side belt transmission.
- ▶ Stamped hammers or Y blades.
- ▶ Hammers guaranteed against breakage.
- ▶ GIROSTOP System.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ Front protection curtain.
- ▶ Obturations antiwire in rotor.
- ▶ Double bearing on rear roller.
- ▶ Rear roller Ø 280 mm.
- ▶ PTO 1.000 rpm.
- ▶ Rear hydraulic hood.
- ▶ Interchangeable counter hammers.
- ▶ Antiwear lining of 4 mm.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35
Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://serrat.nt-rt.ru> || sas@nt-rt.ru



MODEL	mm	KW-HP			KG	N° BELTS TYPE							
							A	A	B	B	C	C	
	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	
T-2800	2800	89 - 120 147 - 200	28	84	2316	2 x 4 XPC	3153	124"	2290	90"	1295	51"	1000
T-3200	3200	104 - 140 147 - 200	32	96	2510	2 x 4 XPC	3553	140"	2290	90"	1295	51"	1000
T-3800	3800	119 - 160 147 - 200	32	96	2845	2 x 4 XPC	4153	163"	2290	90"	1295	51"	1000
T-4600	4600	134 - 180 161 - 220	40	120	3150	2 x 4 XPC	4980	196"	2290	90"	1295	51"	1000
T-6500	6500	149 - 200 198 - 270	56	168	3430	2 x 4 XPC	6880	271"	2290	90"	1295	51"	1000

OPTIONS




▶ Turn able nozzles



▶ Front gums




▶ Hammers




▶ Y blades



▶ Front chains



▶ Freewheel on sleeve



▶ Front skid shoes



▶ Adjustable wheels