



Mulcher for excavators and special carriers having a weight between 3,5 and 6 t.

Steel-plate chassis of 6 mm with the hooking screwed on the top of the mulcher, which reinforce the chassis, giving the possibility of several positions of use.

Suitable for the maintenance of greenspaces, riverbanks, bushes up to 6 cm of diameter.

CHARACTERISTICS

- Non-wear steel-plate chassis, thickness 6 mm.
- Rotor POLSER of Ø 470 mm.
- Mulcher for excavators having a weight between 3,5 and 6 t.
- 3 XPB side belt transmission.
- Double safety chains.
- High speed and high strength bearings.
- Hydraulic gear motor.
- Valve of recirculation incorporated into the motor.
- Front skid shoes.
- Model built under EC Normative.
- Safety indicators visible to personnel.



Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Колмна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93


Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://serrat.nt-rt.ru> || sas@nt-rt.ru

Hydraulic gear motor



Tubular rotor with grass flails or hammers



MODEL	mm	POWER				KG	N° BELTS TYPE	A						max.
		min. req.	max. aut.					A mm	A in	B mm	B in	C mm	C in	
T-600	600	50-80 l/min	250 bar	24	9	262	3 XPB	735	26"	875	34"	645	25"	2500
T-800	800	50-80 l/min	250 bar	32	9	298	3 XPB	935	37"	875	34"	645	25"	2500
T-1000	1000	50-80 l/min	250 bar	40	12	336	3 XPB	1135	45"	875	34"	645	25"	2500
T-1200	1200	50-80 l/min	250 bar	48	12	373	3 XPB	1335	53"	875	34"	645	25"	2500

OPTIONS

