



Forestry heavy duty brush culter with unit-body construction of 15 mm of thickness. Gearbox up to 160 HP.

Suitable for work of clearing brush, creation of grassland, fallow fields and electrical lines, with bushes in foot up to 8 cm.

Frame with unit-body construction. Top reinforcements and plates antispoil low, to avoid the shock of the chains against the chassis. Plate with system of anchorage of chains with linkage parts.

CHARACTERISTICS

- Steel-plate closed or open chassis, thickness 15 mm + 10 mm.
- PTO 1.000 rpm.
- SERRAT rotor with 4 chains with links of Ø 16 mm.
- Front protection curtain.
- Lower reinforcements (links of chains).
- Top reinforcements.
- Transmission with freewheel.
- High-power gearbox.
- Model built under EC Normative.
- Safety indicators visible to personnel.



Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижегород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-94-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://serrat.nt-rt.ru> || sas@nt-rt.ru

SERRAT plate with interchangeable chains



MODEL

	mm	KW-HP	Ø	Ud.		A mm	A in	B mm	B in	C mm	C in	
T-1400	1400	60 - 80 119 - 160	16	4	1031	1757	69"	1860	73"	1615	64"	1000
T-1600	1600	67 - 90 119 - 160	16	4	1184	1957	77"	2050	81"	1615	64"	1000
T-1800	1800	75 - 100 119 - 160	16	4	1318	2160	85"	2200	87"	1615	64"	1000
T-2000	2000	82 - 110 119 - 160	16	4	1435	2357	93"	2305	91"	1615	64"	1000

SERIE

- FXC Closed: There is avoided the dispersion of the crushed material, obtaining a very thing work.

OPTIONS

- FXC Opened: it allows to attack big volumes.
- FXC Rear Hydraulic hood: Combines the two existing working conditions of the previous designs with an hydraulic opening and closing rear hood.

