



Biogreen mulcher, in just one operation and with the usual speed is able to cut and launch the grass and branches to a deposit to remove them from the ground.

With this special application SERRAT wants to contribute to the maintenance of natural areas, roadsides and abores all. wetlands exporting the remains directly to a deposit or a trailer.

## CHARACTERISTICS

- ▶ Non-wear steel-plate chassis, thickness 8 mm.
- ▶ Rotor POLSER of Ø 600 mm.
- ▶ Gearbox SERRAT.
- ▶ 5 XPC side belt transmission.
- ▶ GIROSTOP System.
- ▶ Steel counter hammers.
- ▶ Reaction and impulse turbine with independant transmission.
- ▶ PTO 1.000 rpm.
- ▶ High speed and high strength bearings.
- ▶ Front protection curtain.
- ▶ Obturations antiwire in rotor.
- ▶ Steel worm screw Ø 300 mm.
- ▶ Supports of bearing rotor in steel.
- ▶ Forged hammers SERRAT special "grass".
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



Алматы (7273)495-231  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89  
Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81  
Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47  
Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35  
Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://serrat.nt-rt.ru> || [sas@nt-rt.ru](mailto:sas@nt-rt.ru)

Recivering about 98% of the product from the ground



Obturations antiwire in rotor




Unloading to the ground



Lateral view.  
Settings on high flotation tractor



| MODEL  | <br>mm | <br>KW-HP |  | <br>KG | N° BELTS<br>TYPE |  |         |         |         |         |         |  |
|--------|---------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|------------------|---------------------------------------------------------------------------------------|---------|---------|---------|---------|---------|---------------------------------------------------------------------------------------|
|        |                                                                                             |                                                                                                |                                                                                       |                                                                                             |                  | A<br>mm                                                                               | A<br>in | B<br>mm | B<br>in | C<br>mm | C<br>in |                                                                                       |
| T-2000 | 2000                                                                                        | 59 - 80<br>88 - 120                                                                            | 16                                                                                    | 1505                                                                                        | 5 XPC            | 2460                                                                                  | 97"     | 1150    | 45"     | 950     | 37"     | 1000                                                                                  |
| T-2300 | 2300                                                                                        | 59 - 80<br>88 - 120                                                                            | 20                                                                                    | 1700                                                                                        | 5 XPC            | 2760                                                                                  | 109"    | 1150    | 45"     | 950     | 37"     | 1000                                                                                  |

## OPTIONS

- ▶ Second turbine

